

AMENDMENT TO THE CLAIMSSub
C.7

1. (Currently Amended) A multi-beam scanning optical apparatus

comprising:

incident optical means for making a plurality of light beams emitted from light source means having a plurality of light emitting portions incident on deflection

means; and

scanning optical means for forming images of the plurality of light beams deflected by said deflection means on a surface to be scanned,

wherein said scanning optical means has at least one scanning optical element made of a resin, and said scanning optical element made of the resin has birefringence due to a stress distribution generated upon cooling in a molding process thereof such that the directions of principal axes of birefringence at one end portion of said scanning optical element made of the resin are different from those at the other end portion, opposite to said one end portion with respect to an optical axis thereof in a main scanning direction, of said scanning optical element made of the resin, and

wherein an interval between adjacent scanning lines of scanning lines formed on the ~~scanning~~ scanned surface by the plurality of light beams whose images are formed on the ~~scanning~~ scanned surface through said scanning optical element made of the resin changes in the main scanning direction in an effective scanning region, and

wherein said apparatus comprises at least one setting means for setting a ~~sub-scanning~~ an interval error between the scanning lines in a ~~sub-scanning line direction~~ due to a polarization angle difference between, the interval error being caused by a relation

B

Sub
Cont

in which polarized light beams of the light beams emitted from the plurality of light emitting portions are not parallel or orthogonal with each other, to be not more than 1/5 of a desired scanning line interval.

Cont
B1

2. (Currently Amended) An apparatus according to claim 1, wherein the directions of the principal axes of the birefringence at the end portions of said scanning optical element made of the resin form an asymmetrical distribution due to the stress distribution generated upon cooling in the molding process of said scanning optical element made of the resin.

3. (Original) An apparatus according to claim 1, wherein said apparatus has a plurality of scanning optical elements made of the resin.

4. (Original) An apparatus according to claim 1, wherein said scanning optical means includes refractive optical elements all of which are scanning optical elements made of a resin.

5. (Original) An apparatus according to claim 1, wherein said scanning optical means includes a scanning optical element made of glass.

6. (Original) An apparatus according to claim 1, wherein said scanning optical means includes a reflecting optical element having a power.

Sub
Cont

7. (Original) An apparatus according to claim 1, wherein said setting means sets the polarization angle difference between the light beams emitted from the plurality of light emitting portions to be not more than 20°.

8. (Original) An apparatus according to claim 1, wherein said setting means comprises correction means for correcting the polarization angle difference between the plurality of light beams incident on said scanning optical element made of the resin.

9. (Original) An apparatus according to claim 8, wherein said correction means comprises polarized light limiting means inserted into an optical path between the light source means and said scanning optical element made of the resin.

10. (Original) An apparatus according to claim 9, wherein said polarized light limiting means is tilted with respect to the optical axis of said incident optical means.

11. (Original) An apparatus according to claim 1, wherein the plurality of light emitting portions are independently arranged.

12. (Original) An apparatus according to claim 11, wherein said setting means comprises adjustment means capable of independently adjusting polarization angles of the light beams emitted from the plurality of light emitting portions.

B

Sub
Cmt

13. (Original) An apparatus according to claim 1, wherein the light source means comprises a monolithic multi-beam light source.

14. (Original) An apparatus according to claim 13, wherein said apparatus has a plurality of monolithic multi-beam light sources.

15. (Original) An apparatus according to claim 14, wherein said setting means comprises adjustment means capable of independently adjusting polarization angles of the light beams emitted from the plurality of monolithic multi-beam light sources.

16. (Currently Amended) An apparatus according to claim 1, wherein said setting means comprises a scanning optical element made of a resin, which is shift-decentered perpendicularly to a sub scanning direction and/or rotary-decentered about the main scanning direction.

17. (Original) An apparatus according to claim 1, wherein letting h be a sub-scanning width of said scanning optical element made of the resin and d be an optical-axis-direction width, $h/d \leq 1.8$ is satisfied.

18. (Original) An apparatus according to claim 1, wherein letting h be a sub-scanning width of said scanning optical element made of the resin and t be a sub-scanning width of the light beam passing through said scanning optical element made of the resin, $h/t \leq 15$ is satisfied.

Sub
Cmt

19. (Currently Amended) An image forming apparatus comprising:
a multi-beam scanning optical apparatus according to ~~any one of claims 1 to~~
18 claim 1;
a photosensitive member disposed in the ~~scanning~~ scanned surface;
a developer for developing, as a toner image, an electrostatic latent image
formed on said photosensitive member by light beams scanned by said multi-beam
scanning optical apparatus;
a transfer device for transferring the developed toner image onto a recording
medium; and
a fixing device for fixing the transferred toner image on the recording
medium.

20. (Currently Amended) An image forming apparatus comprising:
said multi-beam scanning optical apparatus of ~~any one of claims 1 to 18~~
claim 1; and
a printer controller for converting code data received from an external
device into an image signal and inputting the image signal to said scanning optical
apparatus.

21. (Cancelled)

22. (Cancelled)

B

Sub
Cmt

23. (Cancelled)

23

24. (Currently Amended) A multi-beam scanning optical apparatus

comprising:

incident optical means for making a plurality of light beams emitted from light source means having a plurality of light emitting portions incident on deflection means; and

scanning optical means for forming images of the plurality of light beams deflected by said deflection means on a surface to be scanned,

wherein said scanning optical means has at least one scanning optical element made of a resin, and said scanning optical element made of the resin has birefringence due to a stress distribution generated upon cooling in a molding process thereof such that the directions of principal axes of birefringence at one end portion of said scanning optical element made of the resin are different from those at the other end portion, opposite to said one end portion with respect to an optical axis thereof in a main scanning direction, of said scanning optical element made of the resin, and

wherein an interval between adjacent scanning lines of scanning lines formed on the ~~scanning~~ scanned surface by the plurality of light beams whose images are formed on the ~~scanning~~ scanned surface through said scanning optical element made of the resin changes in the main scanning direction in an effective scanning region, and

said apparatus comprises at least one setting means for setting a sub-scanning interval error between the scanning lines due to a polarization angle

B

Sub
C. ent
difference between the light beams emitted from the plurality of light emitting portions to be not more than 1/5 of a desired scanning line interval,

Cont
BT
said setting means comprising correction means for correcting the polarization angle difference between the plurality of light beams incident on said scanning optical element made of the resin, and

wherein said setting means comprises adjustment means capable of independently adjusting polarization angles of light beams emitted from the plurality of light emitting portions.

25. (Cancelled)

26. (Cancelled)

27. (Cancelled)

28. (Cancelled)

29. (Cancelled)

30. (Cancelled)

31. (Cancelled)

24
32. (Currently Amended) A multi-beam scanning optical apparatus comprising:

incident optical means for making a plurality of light beams emitted from light source means having a plurality of light emitting portions incident on deflection means; and

B

Sub
C1
cont

scanning optical means for forming images of the plurality of light beams deflected by said deflection means on a surface to be scanned,

wherein said scanning optical means has at least one scanning optical element made of a resin, and said scanning optical element made of the resin has birefringence due to a stress distribution generated upon cooling in a molding process thereof such that the directions of principal axes of birefringence at one end portion of said scanning optical element made of the resin are different from those at the other end portion, opposite to said one end portion with respect to an optical axis thereof in a main scanning direction, of said scanning optical element made of the resin, and

wherein an interval between adjacent scanning lines of scanning lines formed on the ~~scanning~~ scanned surface by the plurality of light beams whose images are formed on the ~~scanning~~ scanned surface through said scanning optical element made of the resin changes in the main scanning direction in an effective scanning region, and

said apparatus comprises at least one setting means for setting an actual sub-scanning interval error between the scanning lines on the scanning surface to be smaller than the sub-scanning interval error between the scanning lines on the ~~scanning~~ scanned surface, caused by a relative displacement in polarization angle between the light beams emitted from the plurality of light emitting portions,

said setting means comprising a scanning optical element made of a resin, which is shift-decentered perpendicularly to a sub scanning direction and/or rotary decentered about the main scanning direction.

B

Sub
Cmt

23

33. (Currently Amended) An image forming apparatus comprising:
a multi-beam scanning optical apparatus according to claim 32;
a photosensitive member disposed in the ~~scanning~~ scanned surface;
a developer for developing, as a toner image, an electrostatic latent image formed on said photosensitive member by light beams scanned by said multi-beam scanning optical apparatus;
a transfer device for transferring the developed toner image onto a recording medium; and
a fixing device for fixing the transferred toner image on the recording medium.

Cmt
B1

24

34. (Original) An image forming apparatus comprising:
said multi-beam scanning optical apparatus of claim 32; and
a printer controller for converting code data received from an external device into an image signal and inputting the image signal to said scanning optical apparatus.

25

35. (Currently Amended) A multi-beam scanning optical apparatus comprising:
incident optical means for making a plurality of light beams emitted from light source means having a plurality of light emitting portions incident on deflection means; and

B

Sub
Cmnt

scanning optical means for forming images of the plurality of light beams deflected by said deflection means on a surface to be scanned,

wherein said scanning optical means has at least one scanning optical element made of a resin, and said scanning optical element made of the resin has birefringence due to a stress distribution generated upon cooling in a molding process thereof such that the directions of principal axes of birefringence at one end portion of said scanning optical element made of the resin are different from those at the other end portion, opposite to said one end portion with respect to an optical axis thereof in a main scanning direction, of said scanning optical element made of the resin, and

wherein an interval between adjacent scanning lines of scanning lines formed on the ~~scanning~~ scanned surface by the plurality of light beams whose images are formed on the ~~scanning~~ scanned surface through said scanning optical element made of the resin changes in the main scanning direction in an effective scanning region, and

said apparatus comprises at least one setting means for setting an actual sub-scanning interval error between the scanning lines on the ~~scanning target~~ scanned surface to be smaller than the sub-scanning interval error between the scanning lines on the ~~scanning~~ scanned surface, caused by a relative displacement in polarization angle between the light beams emitted from the plurality of light emitting portions,

said setting means comprising polarized light limiting means inserted into an optical path between the light source means and said scanning optical element made of the resin.

B

Sub
C: cmt

28

36. (Currently Amended) An image forming apparatus comprising:

a multi-beam scanning optical apparatus according to claim 27;

a photosensitive member disposed in the scanning scanned surface;

a developer for developing, as a toner image, an electrostatic latent image formed on said photosensitive member by light beams scanned by said multi-beam scanning optical apparatus;

a transfer device for transferring the developed toner image onto a recording medium; and

a fixing device for fixing the transferred toner image on the recording medium.

29

37. (Original) An image forming apparatus comprising:

said multi-beam scanning optical apparatus of claim 27; and

a printer controller for converting code data received from an external device into an image signal and inputting the image signal to said scanning optical apparatus.

33

38. (Currently Amended) A multi-beam scanning optical apparatus

comprising:

an incident optical system for making a plurality of light beams emitted from a light source having a plurality of light emitting portions incident on a deflector;

a scanning optical system for forming images of with the plurality of light

B

Sub
C, cont

beams deflected by the deflector on a surface to be scanned, said scanning optical system having a plurality of scanning optical elements each made of a resin; and

at least one setting means for setting ~~a sub-scanning an~~ interval error between scanning lines in a sub-scanning line direction ~~due to a polarization angle difference between~~, the interval error being caused by a relation in which polarized light beams of the light beams emitted from the plurality of light emitting portions are not parallel or orthogonal with each other, to be not more than 1/5 of a desired scanning line interval.

Cont
B1

34' 33' 39. (Previously Added) An apparatus according to claim 38, wherein said scanning optical system includes a reflecting optical element having a power.

35' 33' 40. (Previously Added) An apparatus according to claim 38, wherein said setting means sets the polarization angle difference between the light beams emitted from the plurality of light emitting portions to be not more than 20°.

36' 33' 41. (Previously Added) An apparatus according to claim 38, wherein said setting means comprises a correction system for correcting the polarization angle difference between the plurality of light beams incident on the plurality of scanning optical elements made of the resin.

Sub
Cmt

37' 42. (Previously Added) An apparatus according to claim 41, wherein the correction system comprises a polarized light limiter inserted into an optical path between the light source and the plurality of scanning optical elements made of the resin.

38' 43. (Previously Added) An apparatus according to claim 42, wherein said polarized light limiter is tilted with respect to an optical axis of said incident optical system.

39' 44. (Previously Added) An apparatus according to claim 38, wherein the plurality of light emitting portions are independently arranged.

40' 45. (Currently Amended) An apparatus according to claim 38, wherein said setting means comprises an adjustment system capable of independently adjusting polarization angles of the light beams emitted emitted from the plurality of a light emitting portions.

41' 46. (Previously Added) An apparatus according to claim 38, wherein the light source comprises a monolithic multi-beam light source.

42' 47. (Previously Added) An apparatus according to claim 46, wherein said apparatus has a plurality of monolithic multi-beam light sources.

B

Sub
Cont

43

42

48. (Previously Added) An apparatus according to claim 47, wherein said setting means comprises an adjustment system capable of independently adjusting polarization angles of the light beams emitted from the plurality of monolithic multi-beam light sources.

44

33

49. (Currently Amended) An apparatus according to claim 38, wherein said setting means comprises a scanning optical element made of a resin, which is shift-decentered perpendicularly to a sub-scanning direction and/or rotary-decentered about a main scanning direction.

45

33

50. (Previously Added) An apparatus according to claim 38, wherein letting h be a sub-scanning width of the plurality of scanning optical elements made of the resin and d be an optical-axis-direction width thereof, $h/d \leq 1.8$ is satisfied.

46

33

51. (Previously Added) An apparatus according to claim 38, wherein letting h be a sub-scanning width of the plurality of scanning optical elements made of the resin and t be a sub-scanning width of the light beam passing through the plurality of scanning optical elements made of the resin, $h/t \leq 1.5$ is satisfied.

47

52. (Currently Amended) An image forming apparatus comprising:

33, a multi-beam scanning optical apparatus according to ~~any one of claims 38 to 51~~ claim 38;

B

Sub,
Cont

a photosensitive member disposed in the ~~scanning~~ scanned surface;
a developer for developing, as a toner image, an electrostatic latent image formed on said photosensitive member by light beams scanned by said multi-beam scanning optical apparatus;
a transfer device for transferring the developed toner image onto a recording medium; and
a fixing device for fixing the transferred toner image on the recording medium.

Cont
BT

48

53. (Currently Amended) An image forming apparatus comprising:
a multi-beam scanning optical apparatus according to ~~any one of claims 38 to 51~~ claim 38; and

a printer controller for converting code data received from an external device into an image signal and inputting the image signal to said multi-beam scanning optical apparatus.

51

54. (Currently Amended) A multi-beam scanning optical apparatus comprising:

an incident optical system for making a plurality of light beams emitted from a light source having a plurality of light emitting portions incident on a deflector;

a scanning optical system for forming images of the plurality of light beams deflected by the deflector on a surface to be scanned, said scanning optical system having

B

Sub
C1
Cont refractive optical elements all of which are scanning optical elements each made of a resin;

and

at least one setting means for setting a ~~sub-scanning~~ an interval error between scanning lines in a sub-scanning line direction ~~due to a polarization angle difference between~~, the interval error being caused by a relation in which polarized light beams of the light beams emitted from the plurality of light emitting portions are not parallel or orthogonal with each other, to be not more than 1/5 of a desired scanning line interval.

52 / 51 -
55. (Previously Added) An apparatus according to claim 54, wherein said scanning optical system includes a reflecting optical element having a power.

53 / 51 -
56. (Previously Added) An apparatus according to claim 54, wherein said setting means sets the polarization angle difference between the light beams emitted from the plurality of light emitting portions to be not more than 20°.

54 / 51 -
57. (Previously Added) An apparatus according to claim 54, wherein said setting means comprises a correction system for correcting the polarization angle difference between the plurality of light beams incident on the scanning optical elements made of the resin.

B

Sub
C. cont

58. (Previously Added) An apparatus according to claim 57, wherein the correction system comprises a polarized light limiter inserted into an optical path between the light source and the scanning optical elements made of the resin.

59. (Previously Added) An apparatus according to claim 58, wherein the polarized light limiter is tilted with respect to an optical axis of said incident optical system.

60. (Previously Added) An apparatus according to claim 59, wherein the plurality of light emitting portions are independently arranged.

61. (Previously Added) An apparatus according to claim 60, wherein said setting means comprises an adjustment system capable of independently adjusting polarization angles of the light beams emitted from the plurality of light emitting portions.

62. (Previously Added) An apparatus according to claim 61, wherein the light source comprises a monolithic multi-beam light source.

63. (Previously Added) An apparatus according to claim 62, wherein said apparatus has a plurality of monolithic multi-beam light sources.

B

Sub
Cont

64. (Previously Added) An apparatus according to claim 53, wherein said setting means comprises an adjustment system capable of independently adjusting polarization angles of the light beams emitted from the plurality of monolithic multi-beam light sources.

65. (Currently Amended) An apparatus according to claim 54, wherein said setting means comprises a scanning optical element made of a resin, which is shift-decentered perpendicularly to a sub-scanning direction and/or rotary-decentered about the main scanning direction.

66. (Previously Added) An apparatus according to claim 54, wherein letting h be a sub-scanning width of the scanning optical elements made of the resin and d be an optical-axis-direction width thereof $h/d \leq 1.8$ is satisfied.

67. (Previously Added) An apparatus according to claim 54, wherein letting h be a sub-scanning width of the scanning optical elements made of the resin and t be a sub-scanning width of the light beam passing through the scanning optical elements made of the resin, $h/t \leq 15$ is satisfied.

68. (Currently Amended) An image forming apparatus comprising:
a multi-beam scanning optical apparatus according to any one of claims 54 to 66 claim 54;

B

Sub
C. cont

a photosensitive member disposed in the scanning scanned surface;
 a developer for developing, as a toner image, an electrostatic latent image
 formed on said photosensitive member by light beams scanned by said multi-beam
 scanning optical apparatus;
 a transfer device for transferring the developed toner image onto a recording
 medium; and
 a fixing device for fixing the transferred toner image on the recording
 medium.

Cont
151

66 -

69. (Currently Amended) An image forming apparatus comprising:

51 a multi-beam scanning optical apparatus according to any one of claims 54
 to 66 claim 54; and

a printer controller for converting code data received from an external
 device into an image signal and inputting the image signal to said multi-beam scanning
 optical apparatus.

30 -

23 - 24 - 27 -

70. (Currently Amended) An apparatus according to any one of claims 21,
 24, 29, 32 and 35, wherein said scanning optical system has a plurality of scanning optical
 elements each made of a resin.

23 - 24 - 27 - 31 -

71. (Currently Amended) An apparatus according to any one of claims 21,
 24, 29, 32 and 35, wherein said scanning optical system has refractive optical elements all

B

Sub
C (cont)

of which are the scanning optical elements each made of the resin.

21 /
72. (New) An apparatus according to claim 1, wherein said setting means comprises a scanning optical element made of a resin, which is rotary-decentered about the main scanning direction.

22 /
73. (New) An apparatus according to claim 1, wherein said setting means comprises a scanning optical element made of a resin, which is shift-decentered perpendicularly to a sub scanning direction and rotary-decentered about the main scanning direction.

Cont
B1

69 /
74. (New) A multi-beam scanning optical apparatus comprising:
incident optical means for making a plurality of light beams emitted from light source means having a plurality of light emitting portions incident on deflection means; and
scanning optical means for forming images of the plurality of light beams deflected by said deflection means on a surface to be scanned,
wherein said scanning optical means has at least one scanning optical element made of a resin, and said scanning optical element made of the resin has birefringence due to a stress distribution generated upon cooling in a molding process thereof such that the directions of principal axes of birefringence at one end portion of said scanning optical element made of the resin are different from those at the other end portion,

Sub
Ent

opposite to said one end portion with respect to an optical axis thereof in a main scanning direction, of said scanning optical element made of the resin, and

wherein an interval between adjacent scanning lines of scanning lines formed on the scanned surface by the plurality of light beams whose images are formed on the scanned surface through said scanning optical element made of the resin changes in the main scanning direction in an effective scanning region, and

Car
B

said apparatus comprises at least one setting means for setting an actual sub-scanning interval error between the scanning lines on the scanning surface to be smaller than the sub-scanning interval error between the scanning lines on the scanned surface, caused by a relative displacement in polarization angle between the light beams emitted from the plurality of light emitting portions,

said setting means comprising a scanning optical element made of a resin, which is rotary-decentered about the main scanning direction.

70 /

75. (New) A multi-beam scanning optical apparatus comprising:

incident optical means for making a plurality of light beams emitted from light source means having a plurality of light emitting portions incident on deflection means; and

scanning optical means for forming images of the plurality of light beams deflected by said deflection means on a surface to be scanned,

wherein said scanning optical means has at least one scanning optical element made of a resin, and said scanning optical element made of the resin has

Sub
Cm

birefringence due to a stress distribution generated upon cooling in a molding process thereof such that the directions of principal axes of birefringence at one end portion of said scanning optical element made of the resin are different from those at the other end portion, opposite to said one end portion with respect to an optical axis thereof in a main scanning direction, of said scanning optical element made of the resin, and

wherein an interval between adjacent scanning lines of scanning lines formed on the scanned surface by the plurality of light beams whose images are formed on the scanned surface through said scanning optical element made of the resin changes in the main scanning direction in an effective scanning region, and

Cont
BT

said apparatus comprises at least one setting means for setting an actual sub-scanning interval error between the scanning lines on the scanning surface to be smaller than the sub-scanning interval error between the scanning lines on the scanned surface, caused by a relative displacement in polarization angle between the light beams emitted from the plurality of light emitting portions,

said setting means comprising a scanning optical element made of a resin, which is shift-decentered perpendicularly to a sub scanning direction and rotary-decentered about the main scanning direction.

24, 71, 76, 70, 74, 75

26. (New) A multi-beam scanning optical apparatus according to any one of claims 32, 74, and 75, wherein said setting means sets an interval error between scanning lines in a sub-scanning line direction, the interval error being caused by a relation in which polarized light beams of the light beams emitted from the plurality of light

B

Sub
Cont
emitting portions are not parallel or orthogonal with each other, to be not more than 1/5 of a desired scanning line interval.

27. (New) A multi-beam scanning optical apparatus according to claim 25, wherein said setting means sets an interval error between scanning lines in a sub-scanning line direction, the interval error being caused by a relation in which polarized light beams of the light beams emitted from the plurality of light emitting portions are not parallel or orthogonal with each other, to be not more than 1/5 of a desired scanning line interval.

49-
33-
78. (New) An apparatus according to claim 38, wherein said setting means comprises a scanning optical element made of a resin, which is rotary-decentered about a main-scanning direction.

50-
33-
79. (New) An apparatus according to claim 38, wherein said setting means comprises a scanning optical element made of a resin, which is shift-decentered perpendicularly to a sub-scanning direction and rotary-decentered about a main-scanning direction.

67-
51-
80. (New) An apparatus according to claim 34, wherein said setting means comprises a scanning optical element made of a resin, which is rotary-decentered about the main-scanning direction.

B

Sub
Cont
Cond
B1

151'

81. (New) An apparatus according to claim 74, wherein said setting means comprises a scanning optical element made of a resin, which is shift-decentered perpendicularly to a sub-scanning direction and rotary-decentered about the main-scanning direction.
